International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056
Volume: 12 Issue: 12 | Dec 2025 www.irjet.net p-ISSN: 2395-0072

Smart Solar Energy Systems: A Review of Intelligent Monitoring and Optimization Technologies

Dhananjay Sharma[1], Asst. Prof. Rajshri Pote[2], Vivek Sotra[3], Kapil Prajapati[4], Asmit Hade[5], Yash Chavhan[6]

[2]Assistant Professor, CSE, Priyadarshini College of Engineering Nagpur, Maharashtra, India
[13456]UG Student, CSE, Priyadarshini College of Engineering Nagpur, Maharashtra, India

---

Abstract - *In the global shift to renewable energy, solar photovoltaic (PV) technology has emerged as a key component. Despite its widespread adoption, conventional PV systems still struggle to maintain optimal output due to environmental stressors, inefficient maintenance, temperature rise, and limited operational intelligence. By combining Internet of Things (IoT) monitoring, machine learning (ML), artificial intelligence (AI), automated cleaning, thermal management, and cutting-edge solar materials like lead-free perovskites, the new idea of Solar IQ-Smart systems introduces a paradigm shift and builds a more intelligent and adaptable solar ecosystem. Research from recent years demonstrates that intelligent solar systems can enhance overall performance by approximately 20–40%, restore 25–40% of efficiency losses caused by dust, reduce maintenance costs by up to 30%, and achieve highly accurate generation forecasting exceeding 95%. Although laboratory conversion is still lower, lead-free perovskite materials exhibit simulated efficiencies that are close to 29%. The technological developments, performance enhancements, regional adaptation requirements, and economic models detailed in earlier scholarly investigations are summarized in this review of the literature. Additionally, it presents a critical reflection on current technological gaps while identifying future opportunities for optimization and large-scale deployment. Together, the results highlight the potential of Solar IQ-Smart systems to convert solar PV from a static power-producing structure into an intelligent, self-optimizing energy infrastructure appropriate for utility-scale, commercial, and residential installations.*

Key Words: Smart solar systems, Photovoltaic optimization, Internet of Things (IoT), Artificial intelligence and machine learning, Automated solar panel cleaning, Thermal management, Perovskite solar cells.

1. INTRODUCTION

Due to growing energy demand, growing concerns about climate change, and the depletion of non-renewable resources, the global energy landscape has continuously shifted toward environmentally sustainable power sources. Because of its scalability, small operating footprint, and suitability for a variety of climatic zones, solar power—especially through photovoltaic modules—has emerged as one of the most practical long-term solutions. While the global installed solar capacity continues to exceed terawatt levels, a significant gap persists between the theoretical efficiency of PV modules and their actual field performance.

Due to operational and environmental issues, solar PV panels suffer significant performance degradation. Research indicates that semiconductor efficiency is reduced by 0.38–0.5% per degree Celsius above standard testing conditions.

These restrictions call for the creation of more sophisticated, automated, and user-friendly charging systems.

A viable substitute is provided by wireless power transfer (WPT) technology, especially when it comes to inductive coupling. Wireless EV charging solutions improve safety, convenience of use, and eliminate the need for physical connectors by enabling contactless energy transmission. These systems can provide smooth and continuous charging experiences when integrated into residential garages, parking lots, or roads.

Despite its benefits, wireless charging has drawbacks such alignment sensitivity, inefficient energy transmission, and a lack of intelligent control. The Internet of Things' (IoT) integration is crucial in this situation. Wireless EV charging is not only possible but also very effective and intelligent because to IoT's real-time monitoring, remote control, user identification, predictive maintenance, and smart energy management capabilities. During high-irradiation hours, solar panels in hot regions may reach surface temperatures of 70–75°C, which can cause performance losses of 20–30% over the course of the operating period. In addition to thermal stress, dust accumulation on PV surfaces can obstruct solar radiation and cause energy losses in arid climates that range from 30% to 50% in just one month. Inconsistent maintenance schedules result from the labor and water consumption issues associated with manual cleaning. Likewise, the traditional monitoring of solar infrastructure through basic SCADA systems cannot ensure predictive diagnostics or autonomous optimization. In response to such limits,

the solar energy research community has started to explore solutions that extend beyond panel design and toward system-level intelligence. In order to actively interact with external circumstances and self-correct performance faults, modern intelligent solar systems incorporate sophisticated monitoring, automation, predictive algorithms, intelligent cooling mechanisms, and new material advances. Rather than working just as passive sunlight-to-electricity converters, solar systems are increasingly advancing into self-regulating frameworks capable of automated decision-making, continual optimization, and preventive maintenance.

This research study investigates the developmental trajectory, functionality, and multi-dimensional impact of Solar IQ-Smart systems. It examines research covering cooling and thermal management technologies, automated dust-mitigation methods, IoT-enabled data collecting, artificial intelligence-powered prediction tools, and new photovoltaic materials.

Furthermore, the review critically assesses system-level performance outcomes, economic feasibility, cross-regional adaptability, and unresolved research problems. The data collectively imply that solar energy is shifting toward a future defined not only by better efficiency but by autonomous resilience and sophisticated operational control.

2. EVOLUTION AND CONCEPT OF INTELLIGENT SOLAR SYSTEM

In the past, improvements in semiconductor efficiency were the main emphasis of PV technology developments. However, a turning point occurred when researchers determined that field-level environmental disturbances were the major reason behind energy losses rather than just material inefficiencies. The Solar IQ-Smart concept originated as an interdisciplinary solution combining the areas of power electronics, computational intelligence, networking, data analytics, mechatronics, predictive maintenance, and material science.

In IQ-Smart solar systems:

- IoT sensors collect high-resolution data on irradiation, voltage, current, temperature, humidity, and dust accumulation.
- Machine learning models analyze patterns to discover potential faults early and optimize operation.
- When deviation thresholds are met, actuators automatically initiate cooling or cleaning procedures.
- While providing thermal energy advantages, hybrid PV-thermal components disperse heat.
- Forecasting, performance benchmarking, and remote visualization are made possible by dashboard platforms.
- New PV materials enhance long-term stability and intrinsic conversion efficiency.

Intelligent solar systems consistently maintain a near-optimal operational state despite variations in external circumstances thanks to the coordinated interaction of various technologies. Over the past five years, these systems have matured from experimental prototypes to deployable commercial architectures designed to connect smoothly into residential and utility-level energy infrastructures.

3. REVIEW OF SIGNIFICANT TECHNOLOGICAL ADVANCEMENTS IN LITERATURE

3.1. Cooling and Thermal Management:

Temperature is one of the most damaging elements affecting PV energy yield. Electron recombination speeds up when semiconductor temperature rises, lowering open-circuit voltage and total output. Numerous studies have looked into ways to lessen the effects of temperature using PV/T hybrid systems, passive cooling, and active cooling.

In order to extract heat from solar panels, active water-cooling solutions circulate water over their surface or backside. The findings of the experiment showed that the panel temperature could be quickly lowered from around 75°C to about 25°C in a matter of minutes while using comparatively little pump power. The energy production is usually improved by 8–15% with these cooling techniques. The key worry concerns water usage, which can be unsustainable in dry locations. In order to recover heat energy for secondary uses like water heating, hybrid photovoltaic-thermal systems make use of embedded thermal exchangers. In contrast to traditional cooling, hybrid systems improve building-level heating efficiency and panel performance without squandering thermal output. Findings from controlled evaluations demonstrate that hybrid PV/T systems deliver 5–10% higher electrical production compared to normal PV modules and significantly enhance domestic hot water contribution. These combined benefits lead to a large increase in overall system energy consumption, proving that thermal-management advances boost both electrical performance and end-use energy efficiency.

3.2. Automated Cleaning and Dust Mitigation

Particularly in desert and industrial settings, dust buildup is a significant factor in the decrease in PV

output. The slow accumulation of airborne particles accelerates the deterioration of materials by blocking incoming solar energy and forming hot spots. Traditionally, hand cleaning has included considerable water use and manpower dependence, limiting cleaning frequency.

Recent automated cleaning advancements, including servo-driven brushes, precision water jets and microcontroller-based control logic, provide a sustainable and scalable solution. Under typical cleaning cycles, contemporary automated systems can remove around 90% of surface dust while using only 35–45 milliliters of water per square meter. These devices restore up to 40% of power loss and minimize overall operational expenditures by as much as 90% across ten-year life cycles.

In addition to immediate efficiency recovery, automated systems reduce safety dangers connected with rooftop cleaning and maintain performance consistency independent of human involvement. Cleaning cycles are further aligned with current needs through data-driven activation based on panel output thresholds or dust sensors, which saves electricity and water.

3.3. IoT-Based Solar Monitoring

IoT-enabled solar monitoring builds the intelligent core of Solar IQ-Smart systems. By integrating sensors, wireless connectivity, online platforms, and real-time analytics, IoT transforms PV systems from passive structures into responsive entities capable of performance awareness. IoT systems typically work through a layered architecture that comprises sensors, communication, cloud computing, and user applications.

Highly detailed visibility of panel and inverter performance is made possible by IoT-based monitoring, which also supports automated alert systems for abnormalities like:

- Sudden power drops from shadow or dust.
- Voltage and current reduction owing to degradation.
- Panel overheating or cooling system failure.
- Electrical discontinuities or problems with connections.
- Unexpected energy variations due to micro-environmental changes.

IoT monitoring has been proved to boost energy yield due to timely adjustment of peak power tracking, scheduling of maintenance during low-production periods, and optimized load balancing. IoT infrastructure deployment expenses are still comparatively inexpensive and are typically recovered with more output and less downtime in one to two years.

3.4. Artificial Intelligence and Machine Learning

Solar system optimization and predictive intelligence are made possible by machine learning. ML models can forecast energy output, estimate future deterioration, identify early failure signs, and schedule maintenance autonomously by analyzing historical and environmental data rather than responding to performance loss.

Studies reveal extraordinarily high forecasting accuracy when employing ensemble and deep learning approaches. Solar irradiation, panel temperature, time of day, past production, and ambient weather indicators are the most important factors for forecasting. With prediction accuracy surpassing 95%, ML models promote grid stability, optimal battery scheduling, and successful energy trading. Moreover, ML-supported predictive maintenance greatly decreases unplanned outages and maintenance expenses.

In the future, federated and reinforcement learning are expected to enable collaborative model training across distributed solar installations while enabling closed-loop optimization without central supervision.

3.5. Perovskite and Advanced Solar Materials

Material innovation remains essential for long-term solar advancement. Perovskite-based solar cells have drawn attention due to their low cost and high theoretical power-conversion potential, despite silicon having dominated the PV industry for decades. Lead-free varieties such as $CsGeI_3$ address toxicity concerns traditionally associated with perovskites.

With conversion efficiencies close to 29%, simulated perovskite architectures have the potential to outperform traditional silicon panels. These materials possess suitable electrical characteristics and improved stability in comparison with earlier perovskite formulations. Despite these breakthroughs, laboratory prototypes still lag behind simulation results, achieving efficiencies between 4.92% and 13.57%. Processing quality, long-term material stability, and industrial scalability remain barriers to commercialization.

However, perovskites are positioned to help tandem panel designs in the future, where silicon is complemented by perovskite layers to increase overall efficiency beyond current limits.

4. PERFORMANCE IMPACT AND SYSTEM-LEVEL INTEGRATION

While individual improvements contribute to performance enhancement, the highest gains are achieved when cooling, automated cleaning, IoT monitoring, and ML prediction are combined into one system.

The interactions among subsystems create a self-reinforcing feedback loop:

- IoT sensors detect changes in output and identify causal factors.
- Predictive algorithms determine if cleaning, cooling, or operational adjustments are needed.
- Automated components activate only when necessary to keep energy stable.
- Collected data improves forecasting models through ongoing learning.

This operational loop leads to:

- More consistent energy production.
- Less mechanical and thermal stress on solar components.
- Longer panel lifespan by avoiding extreme operating conditions.
- Lower cost per kilowatt-hour over the total lifetime usage.
- More reliable financial models for large-scale solar installations.

5. ENVIRONMENTAL SUITABILITY AND REGIONAL ADAPTATION

Geographical and Climatic Impact on Solar IQ-Smart System Performance

Geographical and climatic factors play a crucial role in determining the performance of Solar IQ-Smart systems. Different regions present unique environmental challenges, requiring region-specific technological adaptations. The most effective technologies for various regions are summarized below:

Table-1: Regional Climate Impact on Solar IQ-Smart System Performance

Region Type	Characteristics	Most Effective Technologies
Tropical	High temperature, high humidity, scattered rainfall	Active cooling techniques, corrosion-resistant designs, scheduled cleaning during dry seasons
Arid / Desert	Intense solar radiation, heavy dust accumulation, limited water availability	Automated low-water cleaning systems, dust-triggered activation, solar tracking systems
Temperate	Seasonal variations in temperature, precipitation, and snowfall	PV/T hybrid systems, seasonal tilt adjustment, reduced cleaning frequency
Coastal	Saline humidity and corrosion risk	Anti-corrosion coatings, sealed electronic components, moderate cleaning
High-Altitude	Low temperatures and high UV exposure	Machine learning-based irradiance prediction, passive thermal management

Regardless of regional environmental variability, appropriate adaptation strategies ensure that Solar IQ-Smart installations remain efficient, sustainable, and reliable across diverse climatic conditions.

6. OPERATIONAL AND ECONOMIC VIABILITY

Economic Feasibility of Solar IQ-Smart Systems

For large-scale adoption, Solar IQ-Smart systems must demonstrate strong financial viability. Automated cleaning modules show a payback period of less than one year in dust-prone regions, while investments in IoT-based monitoring systems typically recover costs within one to two years due to improved energy output and reduced maintenance requirements. Hybrid PV/T systems achieve cost recovery within three to five years by combining electrical power generation with thermal energy utilization.

From a revenue perspective, automated cleaning systems alone contribute an average annual energy gain of approximately 18%. Additionally, predictive maintenance enabled by IoT and AI technologies extends component lifespan and minimizes avoidable system failures, further reducing operational costs.

These findings confirm that intelligent solar technologies are not only technically advantageous but also economically competitive within the renewable energy market.

7. RESEARCH GAPS AND FUTURE SCOPE

Despite notable progress, further research is needed in the following areas:

- Automated cleaning systems' long-term environmental resilience when exposed to abrasive dust.
- Lead-free perovskite solar cells' commercial-level lifespan and industrial scalability.

- Power consumption reduction for intelligent systems to guarantee almost zero operational overhead.
- Integration guidelines for IoT and analytics services' cross-platform compatibility.
- Robust cybersecurity architecture for preventing unauthorized access to smart solar networks.
- The creation of widely applicable machine learning models that can adjust to weather anomalies and climate change.

Future research must address these gaps to achieve stable and cost-efficient long-term operation.

8. CONCLUSION

This literature review highlights a transformative trend within the solar energy industry. The shift from passive photovoltaic systems to Solar IQ-Smart systems signals the beginning of an energy ecosystem where automation, data intelligence, material innovation, and machine learning play central roles. Traditional obstacles like heat, dust buildup, neglected maintenance, and inefficient systems are greatly reduced by integrated smart technologies. By enabling self-correcting performance, intelligent solar infrastructure maximizes energy yield, lowers lifecycle costs, and improves long-term reliability.

While additional refinement is needed in areas such as perovskite material stability, automation durability, and cybersecurity, the foundational progress achieved in recent years positions Solar IQ-Smart systems as the next stage of advancement in renewable-energy engineering. It is anticipated that intelligent solar systems will move from optional upgrades to industry-wide standards necessary for supplying the world's energy needs as deployment costs drop and performance gains keep increasing.

REFERENCES

[1] R. Parthiban and P. Ponnambalam, "An enhancement of the solar panel efficiency: A comprehensive review," *Frontiers in Energy Research*, vol. 10, Art. no. 937155, 2022.

[2] W. Charfi, M. Chaabane, H. Mhiri, and P. Bournot, "Performance evaluation of a solar photovoltaic system," *Energy Reports*, vol. 4, pp. 400–406, 2018.

[3] D. Kumari, N. Jaiswal, D. Punetha, S. K. Mourya, and S. K. Pandey, "$CsGeI_3$ perovskite-based solar cells for higher efficiency and stability: An experimental investigation," *IEEE Journal of Photovoltaics*, 2025.

[4] R. Khan *et al.*, "Device modeling and performance enhancement of ecologically viable $CsGeI_3$-based perovskite solar cells: A detailed investigation of charge transport layer technology," *Nano Select*, 2025.

[5] C. Taruna, L. Halim, and B. M. Arthaya, "Initial concept for increasing polycrystalline fixed solar panel efficiency with water treatments," in *Proc. Int. Conf. Mechatronics, Robotics and Systems Engineering (MoRSE)*, 2019, pp. 180–185.

[6] H. Mote *et al.*, "Automatic solar panel cleaning system," *Journal of Automation and Automobile Engineering*, vol. 10, no. 1, pp. 38–46, 2025.

[7] M. Baiceanu, T. Catalina, and A. Damian, "Experimental and simulation performance investigation of a hybrid PV/T solar panel," in *Proc. 7th Int. Conf. Energy Efficiency and Agricultural Engineering (EE&AE)*, 2020, pp. 1–5.

[8] B. Sreewirote, A. Noppakant, and C. Pothisarn, "Increasing efficiency of an electricity production system from solar energy with a method of reducing solar panel temperature," in *Proc. IEEE Int. Conf. Applied System Innovation (ICASI)*, 2017, pp. 1308–1311.

[9] M. A. A. Mamun, M. M. Islam, M. Hasanuzzaman, and J. Selvaraj, "Effect of tilt angle on the performance and electrical parameters of a PV module," *Energy and Built Environment*, vol. 3, pp. 278–290, 2022.

[10] A. H. Alami, "Effects of cooling techniques on photovoltaic module performance in UAE conditions," *Renewable Energy*, vol. 103, pp. 619–628, 2017.

[11] A. Soares, M. França, and P. Mendes, "Passive and active cooling methods for photovoltaic modules: A review," *Energy Reports*, vol. 6, pp. 274–286, 2020.

[12] M. Mani and R. Pillai, "Impact of dust on solar photovoltaic (PV) performance," *Renewable and Sustainable Energy Reviews*, vol. 14, no. 9, pp. 3124–3131, 2010.

[13] R. R. Cordero *et al.*, "Effects of aerosols and dust on PV systems in desert regions," *Solar Energy*, vol. 174, pp. 1190–1200, 2018.

[14] M. Al-Housani, Y. Bicer, and M. Koç, "Assessment of PV cleaning techniques in arid climates," *Energy Conversion and Management*, vol. 186, pp. 71–85, 2019.

[15] S. Mekhilef, R. Saidur, and M. Kamalisarvestani, "Effect of dust, humidity and air quality on PV performance," *Renewable and Sustainable Energy Reviews*, vol. 16, no. 8, pp. 4523–4530, 2012.

[16] H. Rezk and A. M. Eltamaly, "A comprehensive approach for wind and solar power plants monitoring using IoT technologies," *IEEE Systems Journal*, vol. 9, no. 3, pp. 955–965, 2015.

[17] H. Abdul-Ghani, C. Konstantinou, and R. Lopes, "IoT-based monitoring of solar photovoltaic systems," *IEEE Access*, vol. 9, pp. 60174–60192, 2021.

[18] C. Voyant *et al*., "Machine learning methods for solar radiation forecasting," *Renewable Energy*, vol. 105, pp. 569–582, 2017.

[19] S. Sobri, N. Muhamad, and M. Z. A. A. Kadir, "Solar radiation prediction using machine learning models," *Energy Conversion and Management*, vol. 78, pp. 100–110, 2018.

[20] K. Brecl and M. Topič, "Forecasting solar PV performance using deep learning models," *Solar Energy*, vol. 220, pp. 1100–1112, 2021.

[21] S. A. Kalogirou, "Hybrid photovoltaic/thermal (PV/T) solar systems: A review," *Renewable Energy*, vol. 55, pp. 472–481, 2014.

[22] T. T. Chow, "A review on photovoltaic/thermal hybrid solar technology," *Applied Energy*, vol. 87, no. 2, pp. 365–379, 2010.

[23] National Renewable Energy Laboratory, *Photovoltaic System Performance Temperature Coefficients*, NREL Report, 2020.

[24] National Renewable Energy Laboratory, *Best Research-Cell Efficiency Chart*, 2021.