International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056
Volume: 12 Issue: 12 | Dec 2025 www.irjet.net p-ISSN: 2395-0072

Border Surveillance Using Satellite Imagery and Artificial Intelligence

Prof. Shobha S. Biradar[1], Shreyas Gururaj Babaleshwar[2]

[1]*Professor, Master of Computer Applications, VTU CPGS, Kalaburagi, Karnataka, India*
[2]*Student, Master of Computer Applications, VTU CPGS, Kalaburagi, Karnataka, India*

Abstract - *Border surveillance has become a critical national security requirement due to increasing concerns regarding illegal migration, unauthorized crossings, smuggling, and strategic threats. This research proposes a satellite-based, artificial intelligence-driven surveillance system capable of continuously monitoring border regions using multi-temporal remote sensing data. The system integrates Google Earth Engine with intelligent modules for vegetation change analysis (NDVI), movement tracking, object detection (vehicles, buildings, and cargo containers), human footprint tracing, and predictive analytics for smuggling and migration risks. The proposed solution automates geospatial analysis through indices (NDVI, NDBI, NDWI, BSI), SAR backscatter, and temporal differencing. A Stream lit-based dashboard provides real-time analysis, alerts, and risk visualization for border forces. The system is lightweight, scalable, and low-cost, making it suitable for large border surveillance operations. Experimental evaluation shows significant potential for real-time border monitoring, early anomaly identification, and predictive security analytics.*

Key Words: **Satellite Imagery, Google Earth Engine, NDVI, Border Surveillance, AI Analytics, Movement Detection, Predictive Risk Modeling, Object Detection**

1. INTRODUCTION

Border surveillance plays an essential role in national security, especially for countries with extensive geopolitical boundaries. Traditional surveillance techniques depend heavily on human patrolling, CCTV networks, and local sensor systems. These approaches are limited in range, prone to human error, and often infeasible in remote terrains such as deserts, mountains, marshlands, and dense forests. Modern technological advancements have enabled the use of satellite imagery in conjunction with AI to monitor borders at scale, regardless of terrain or climatic conditions. Satellite missions like Sentinel-2 (optical) and Sentinel-1 (SAR) offer high-resolution, frequent, and cloud-penetrating imagery that can reveal surface anomalies, movement patterns, construction activities, and environmental changes. Artificial Intelligence further elevates the value of satellite data by providing automated detection, classification, and prediction capabilities.

This research introduces a unified border surveillance system using **Google Earth Engine (GEE)** and **AI-based analytical modules**, accessible through a user-friendly Streamlit dashboard. The proposed system analyses a selected Area of Interest (AOI) and performs vegetation change mapping, movement analysis, object detection, footprint tracing, desert sandstorm suppression, and predictive risk modelling.
The objective is to provide border security forces with accessible, real-time insights that support operational readiness, strategic decision- making, and preventive security interventions.

1.1 Problem Identification

Current border surveillance systems lack automated, large-scale, terrain-independent reconnaissance capabilities. Manual methods are labor-intensive and fail to detect subtle or low-visibility activities such as gradual encroachment, illegal trails, temporary shelters, or night-time movements. The absence of automated anomaly detection exposes borders to security vulnerabilities.

1.2 Objectives of the Study

1. To develop a satellite-driven AI surveillance dashboard for border monitoring.
2. To implement change detection modules including NDVI, movement tracking, and dust storm masking.
3. To detect vehicles, buildings, cargo containers, and footprints using Earth Engine imagery.
4. To integrate predictive analytics for migration or smuggling-related risk assessment.
5. To provide real-time alerting and intuitive geospatial visualization for authorities.

1.3 Scope

The project can be applied to:

1. International land borders
2. Desert / coastal / mountainous terrains
3. Defense intelligence operations
4. Disaster response and illegal settlement monitoring
5. Smuggling and infiltration detection

1.4 Methodology Overview

Data is retrieved from Sentinel-1 and Sentinel-2 satellite collections. Various indices such as NDVI, NDWI, NDBI, and BSI are computed, along with RGB differencing for movement tracking. SAR backscatter identifies metallic or rigid structures. A predictive model computes risk levels

from satellite-derived features. The results are displayed via a Stream lit dashboard integrated with GEE.

2. LITERATURE SURVEY

Existing border surveillance systems rely primarily on physical patrols, ground sensors, and drone feeds. However, academic studies highlight the potential of satellite-AI methods for large-scale monitoring. Research by Saadi & Samir (2023) explores AI-based border analytics, while Google's Open Buildings dataset provides state-of-the-art building extraction accuracy. Other studies employ NDVI, NDBI, and BSI indices for environmental and movement detection. These works collectively justify the need for automated satellite intelligence systems.

2.1 Existing Systems

Traditional border surveillance involves:

- Physical patrolling
- Border fences and ground sensors
- CCTV monitoring
- UAV and drone patrols

These methods face limitations in large and inaccessible regions, weather dependence, and require large manpower.

- **Limitations**
  - Limited area coverage
  - Risk to human personnel
  - No automated anomaly detection
  - High operational costs

2.2 Proposed System Overview

The proposed system utilizes satellite imagery and AI to automate surveillance. It comprises:

- NDVI-based vegetation monitoring
- Before/After image comparison
- Movement heatmaps
- Object detection: vehicles, buildings, cargo containers
- Footprint mapping using Bare Soil Index
- Dust storm masking
- Predictive risk modelling

This unified approach offers broad coverage, automation, and continuous monitoring capabilities.

2.3 Feasibility Study

- **Technical Feasibility**

Uses cloud-powered Google Earth Engine and lightweight Python libraries, requiring no high-end hardware.

- **Operational Feasibilit10y**

Border forces can easily operate the dashboard due to its simplified UI.

- **Economic Feasibility10**

All satellite datasets used (Sentinel-1, Sentinel-2, Google Open Buildings) are freely accessible.

2.4 Tools and Technologies Used

- Python 3.10, Streamlit, Leafmap, Folium
- Google Earth Engine API
- Scikit-learn, Pandas, NumPy
- Plotly, Matplotlib

3. SOFTWARE REQUIREMENT SPECIFICATION (SRS)

3.1 Users

- Border security forces
- Intelligence analysts
- Disaster management authorities
- Remote sensing researchers

3.2 Functional Requirements

- Detect vegetation loss using NDVI
- Track movement using RGB difference
- Extract buildings using Open Buildings
- Identify vehicles and containers
- Trace footprints using BSI
- Produce risk forecasts

3.3 Non-Functional Requirements

- Real-time response
- Web-based interface
- High accuracy of spectral indices
- Secure access
- Scalability for national-level deployment

4. SYSTEM DESIGN

4.1 Context Diagram



Fig 1: Context Diagram

4.2 System Perspective

The architecture includes three layers:

1. **Data Layer** – Sentinel-1/2, Open Buildings
2. **Processing Layer** – Earth Engine, spectral indices, ML
3. **Application Layer** – Stream lit maps, alerts, graphs



Fig 2: System Architecture

5. IMPLEMENTATION

5.1 System Setup & Environments

This section describes the software, hardware, and environmental requirements used to develop the Border Surveillance Using Satellite and AI system. The implementation uses Python, Stream lit, and Google Earth Engine (GEE) for satellite-based analysis.

5.1.1 Programming Environment

The system is developed in Python 3.10 with Stream lit as the dashboard framework. Google Earth Engine API handles satellite imagery processing, while Leafmap/Geemap render maps. Additional libraries include scikit-learn for model training, Plotly for graph visualization, and Folium for geospatial layers.

5.1.2 Hardware Requirements

The system requires a minimum of an Intel i5 processor, 8 GB RAM, and stable internet connectivity to fetch and process real-time satellite data.

5.2 Module-Wise Implementation

This section explains each module implemented in the surveillance dashboard, along with algorithms and workflows.

5.2.1 NDVI Change Detection

Normalized Difference Vegetation Index (NDVI) is computed using Sentinel-2 bands. A time-series graph and change map highlight vegetation loss or new growth.

5.2.2 Before/After Image Viewer

A split-map slider compares true-color satellite imagery between two selected dates, allowing visual assessment of structural and environmental changes.

5.2.3 Movement Tracking

Movement heatmaps are generated by computing absolute RGB differences between images. Thresholding helps highlight areas with significant activity or structural changes.

5.2.4 Vehicle Detection

Vehicle hotspots are detected by combining NDBI (building suppression), NDWI (vegetation suppression), and SAR backscatter to isolate metallic objects.

5.2.5 Cargo Container Detection

Edge detection algorithms identify linear parallel structures typical of stacked cargo containers in ports or border checkpoints.

5.2.6 Person Footprint Tracing (BSI)

Bare Soil Index (BSI) identifies exposed soil trails that indicate human activity or footpaths in desert regions. NDVI masking removes vegetation noise.

5.2.7 Dust/Sandstorm Masking

SWIR and NIR spectral ratios detect airborne dust or sand, essential for desert border regions. Dust masks improve clarity before feature extraction.

5.2.8 Predictive Risk Modeling

A logistic regression model classifies risk levels (Low/Medium/High) using NDVI trends, movement, dust intensity, and seasonal attributes.

5.3 Integration Workflow

All modules operate through a unified Stream lit dashboard, calling GEE for data retrieval, processing results, and rendering maps interactively.

5.4 Code Snippets (Examples)

NDVI: ndvi = image. Normalized Difference(['B8','B4'])

Movement:
diff=after.subtract(before).abs().reduce(ee.Reducer.sum())

5.5 Frontend Implementation

The dashboard is built using Stream lit, featuring side panels for inputs, dynamic rendering using m.to_ stream lit(), and export options.

5.6 Performance Optimization

Optimization includes using GEE reducers, caching mechanisms, and minimizing heavy computation through efficient filtering.

6. MATHEMATICAL MODEL

This section presents the mathematical foundations used in the "Border Surveillance Using Satellite Imagery and Artificial Intelligence" system. The model combines spectral indices, spatial change detection, and multi-modal risk scoring to quantify terrain activity, movement, and anomalies along border regions.

A. Normalized Difference Vegetation Index (NDVI)

NDVI is used to monitor vegetation health and detect anomalies such as clearing of areas or movement-induced vegetation disturbances.

$$NDVI = \frac{NIR - Red}{NIR + Red} \qquad (1)$$

Where:

- $NIR = B8$ **(Near Infrared)**
- $Red = B4$

A significant drop in NDVI may indicate human activity, vehicle movement, or soil exposure.

B. Normalized Difference Water Index (NDWI)

NDWI is used to suppress vegetation and highlight road surfaces for refined vehicle detection.

$$NDWI = \frac{Green - NIR}{Green + NIR} \qquad (2)$$

Where:

- $Green = B3$
- $NIR = B8$

Values near zero or negative indicate roads, trails, and non-vegetated surfaces.

C. Normalized Difference Built-Up Index (NDBI)

NDBI helps remove buildings from analysis to isolate vehicles and open land features.

$$NDBI = \frac{SWIR - NIR}{SWIR + NIR} \qquad (3)$$

Where:

- $SWIR = B11$
- $NIR = B8$

Higher NDBI values correspond to urban structures, rooftops or construction.

D. Bare Soil Index (BSI) ***(Used for Footprint Tracing)***

The Bare Soil Index enhances features where soil is exposed, including human footprints and illegal paths.

Bare Soil Index (BSI)

$$BSI = \frac{(Red + SWIR) - (NIR + Blue)}{(Red + SWIR) + (NIR + Blue)} \qquad (4)$$

Where:

- **Blue = B2**
- **Red = B4**
- **NIR = B8**
- **SWIR = B11**

Higher BSI values highlight recently disturbed soil.

E. Movement Detection using RGB Difference

Movement is computed by change in surface reflectance.

$$Movement = |(R_2 - R_1)| + |(G_2 - G_1)| + |(B_2 - B_1)| \qquad (5)$$

Where:

- R_1, G_1, B_1**: Before image**
- R_2, G_2, B_2**: After image**

Large values indicate vehicle movement, construction, or surface disturbances.

F. SAR Backscatter Measurement

Sentinel-1 SAR data is used to detect metallic objects such as vehicles or equipment.

$$\sigma^0_{norm} = 10\log_{10}(\sigma^0) \qquad (6)$$

High values → metal signatures
Low values → vegetation or soil

G. Dust & Sand Masking Index

Dust storms are common in desert borders; detection uses thermal and optical band differences:

$$DustIndex = (B11 - B8A) + (B12 - B4) \quad (7)$$

High Dust Index values indicate airborne dust or sand obstructing visibility.

H. Change Detection Model

Generalized formula to detect changes in any index value:

$$\Delta I = I_{after} - I_{before} \quad (8)$$

Where I is any spectral index (NDVI, BSI, NDWI, etc.).

Significant change:

$$\Delta I > T \Rightarrow \text{Alert: Suspicious Activity} \quad (9)$$

T is a threshold selected by the analyst.

I. Binary Threshold Masking

All detection layers use threshold-based classification:

$$Mask(x) = \begin{cases} 1, & x > T \\ 0, & x \leq T \end{cases} \quad (10)$$

This produces clean masks for heatmaps and object detection.

J. Predictive Risk Score Model

The system computes a risk score using weighted satellite-derived features:

$$RiskScore = w_1(NDVI_{drop}) + w_2(Movement) + w_3(BSI_{footprints}) + w_4(SAR_{spikes}) + w_5(DustIndex) \quad (11)$$

Where:

- **$w_1, w_2, \ldots w_5$ = learned model weights**

Risk levels:

$$Risk < 30 \rightarrow Low; 30 \leq Risk < 60 \rightarrow Medium; Risk \geq 60 \rightarrow High \quad (12)$$

This provides near-real-time risk prediction for border activity.

K. Final Mathematical Summary Table

Index / Model	Formula	Purpose
NDVI	(1)	Vegetation loss / illegal clearing
NDWI	(2)	Road & soil highlighting
NDBI	(3)	Building removal
BSI	(4)	Footprint / soil disturbance detection
Movement	(5)	Vehicle & human movement
SAR	(6)	Metal object detection
Dust Index	(7)	Desert preprocessing
Change Map	(8) & (9)	Activity alerts
Risk Model	(11) & (12)	Predictive analytics

7. RESULTS

The system successfully identifies high-change zones, structural modifications, dust storms, human footprints, and container layouts. Predictive models highlight risk probabilities ranging from low to critical based on movement, vegetation, and environmental variables.



Fig 3: NDVI Time Series & alerts



Fig 4: Movement Tracking Heatmap



Fig 5: Refined Vehicle Detection



Fig 6: Cargo Container/ Port Layout Detection



Fig 7: Person Detection/ Footprint Tracing (BSI)



Fig 8: Adaptive Desert Preprocessing and Dust Mask



Fig 9: Predictive Analysis for Migration and Smuggling

8. CONCLUSION

The proposed system demonstrates that satellite-AI integration provides scalable, accurate, and continuous border monitoring. The framework reduces manpower burden and significantly enhances situational awareness for national security.

9. Future Enhancements

- Multi-model deep learning for object classification
- Federated learning for distributed border stations
- Integration with autonomous surveillance robots
- Multi-sensor fusion (thermal + hyperspectral + LiDAR)
- Ethical AI compliance dashboard

REFERENCES

[1] Google Earth Engine Team, "Google Earth Engine: A Planetary Scale Geospatial Analysis Platform," Available: https://earthengine.google.com

[2] A. Gorelick et al., “Google Earth Engine: Planetary-scale geospatial analysis for everyone,” Remote Sensing of Environment, vol. 202, pp. 18–27, 2017.

[3] Sentinel-2 Mission, European Space Agency (ESA), "Copernicus Open Access Hub," Available: https://scihub.copernicus.eu

[4] J. Drusch et al., "Sentinel-2: ESA's optical high-resolution mission for GMES operational services," Remote Sensing of Environment, vol. 120, pp. 25–36, 2012.

[5] Google Research, "Open Buildings Dataset," Available: https://sites.research.google/open-buildings/

[6] N. Jean et al., "Combining satellite imagery and machine learning for poverty prediction," Science, vol. 353, no. 6301, pp. 790–794, 2016.

[7] S. Midekisa et al., "Satellite-based analysis of vegetation health for disease risk prediction," Remote Sensing Applications, vol. 6, pp. 27–38, 2017.

[8] X. Zhang et al., "Change detection techniques for remote sensing applications: A survey," ISPRS Journal of Photogrammetry and Remote Sensing, vol. 115, pp. 110–128, 2016.

[9] T. Blaschke et al., "Object-based image analysis for remote sensing," ISPRS Journal, vol. 65, pp. 2–16, 2014.

[10] F. Bovolo and L. Bruzzone, "A theoretical framework for change detection based on pixel-by-pixel image analysis," IEEE Transactions on Geoscience and Remote Sensing, vol. 45, no. 11, pp. 3894–3906, 2007.

[11] M. Teke et al., "A new approach for dust storm detection using satellite images," Atmospheric Research, vol. 176–177, pp. 241–252, 2016.

[12] J. Torres et al., "SAR-based detection of vehicles and tactical objects," IEEE Transactions on Aerospace and Electronic Systems, vol. 48, no. 2, pp. 1345–1356, 2012.

[13] R. Achanta et al., "A survey of motion detection algorithms from remote sensing," International Journal of Remote Sensing, vol. 41, no. 14, pp. 5606–5631, 2020.

[14] I. Saadi and A. M. Samir, "The Impact of Artificial Intelligence Technology on Border Surveillance: A Comprehensive Analysis," Journal of Border Security Studies, 2023.

[15] Scikit-learn Developers, "Machine Learning in Python," Available: https://scikit-learn.org

[16] Streamlit Team, "Streamlit Documentation," Available: https://docs.streamlit.io

[17] L. Bruzzone and D. F. Prieto, "Automatic analysis of the difference image for unsupervised change detection," IEEE Trans. Geoscience and Remote Sensing, vol. 38, no. 3, pp. 1171–1182, 2000.

[18] A. Singh, "Digital change detection techniques using remotely-sensed data," Int. J. Remote Sensing, vol. 10, no. 6, pp. 989–1003, 1989.

[19] E. N. Anagnostopoulos et al., "Predictive analytics for border security using multi-source data," Security Informatics, vol. 4, no. 6, 2015.

[20] J. Liu et al., "Human footprint detection using BSI and NDVI," Remote Sensing Letters, vol. 11, no. 4, pp. 389–398, 2020.