International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056
Volume: 12 Issue: 12 | Dec 2025 www.irjet.net p-ISSN: 2395-0072

An Inbuilt Car Vacuum Cleaner System

Satish Kona[1], Geetika Dasari[2], Sivakumar Thiruvarasan[3] ,Thangavelu Krishnamoorthy[4]

[1,2,3] *Engineer, Platform, After Sales Engineering, Research & Advance Engineering, Renault Nissan Technology & Business Centre India*

[4] *Manager, Platform, After Sales Engineering, Research & Advance Engineering, Renault Nissan Technology & Business Centre India*

Abstract- *This paper introduces a conceptual approach for an inbuilt car vacuum cleaner system, aiming to transform the way vehicle interiors are cleaned and maintained. Traditional car cleaning relies on external vacuum cleaners or professional services, which can be inconvenient, time-consuming, and costly. To address these challenges, the proposed concept integrates a compact, vehicle-mounted vacuum cleaner that operates directly from the car's existing infrastructure, offering greater convenience and on-demand cleaning capability. The idea focuses on efficient power usage from the vehicle's electrical system, optimal placement of cleaning components, and user-friendly control through the dashboard or infotainment system. Basic features envisioned for this concept include effective suction performance, compact housing, essential filtration mechanisms, and reduced noise to ensure a comfortable user experience. Rather than detailing a full engineering solution, this paper outlines the motivation, conceptual framework, expected benefits, and potential applications of an integrated car vacuum cleaner system, highlighting its role in enhancing everyday vehicle cleanliness and ownership convenience.*

Keywords: **Inbuilt car vacuum cleaner, automotive cleaning system, integrated vehicle features, on-board vacuum concept, interior maintenance, compact suction system, automotive convenience, power-efficient design, filtration system, dashboard-controlled cleaning, vehicle hygiene, innovative car features.**



Figure 1: Inbuilt Car Vacuum System (AI)

1. INTRODUCTION

1.1 Background

Vehicle interior cleaning has traditionally relied on manual methods such as dusting, wiping, and using external vacuum cleaners. In earlier designs, vehicles were not equipped with any built-in mechanism to maintain cleanliness, making the process entirely dependent on human effort. The introduction of portable car vacuum cleaners brought some convenience by allowing users to clean the cabin using compact suction devices. However, these systems still require external setup, power connections, and manual operation. Over time, improvements in suction motors, filtration systems, and battery-powered handheld units have enhanced cleaning performance, yet none have provided a fully integrated solution that operates as part of the vehicle itself. Thus, despite technological progress, interior maintenance remains a time-consuming and repetitive task.

1.2 Current Challenges (External Cleaners, Time, Power Consumption, Cost)

Existing cleaning methods, whether through portable vacuum cleaners or professional services, face several limitations. Portable cleaners often lack sufficient suction power, have limited operating time due to battery constraints, and require users to physically handle the device for every cleaning cycle. Professional car cleaning services, while more effective, demand both time and money, making them impractical for frequent use.

Moreover, portable devices connected through the car's 12 V socket draw significant power, risking electrical overload or battery drain if used for extended periods. This dependency on external tools not only increases operational time but also adds recurring maintenance and replacement costs, creating inconvenience for vehicle owners.

1.3 Motivation for Developing an Inbuilt System

The motivation behind developing an inbuilt car vacuum cleaner system arises from the need for a more efficient, user-friendly, and sustainable vehicle cleaning solution. In modern urban environments, vehicles are exposed daily to dust, pollution, and debris, which accumulate quickly inside the cabin. Relying on external cleaning devices or periodic services is neither practical nor consistent for maintaining

hygiene. Integrating a compact, power-optimized cleaning system within the vehicle structure allows users to perform quick cleaning operations anytime, without external support. This approach also aligns with the automotive industry's trend towards smart, automated, and comfort-enhancing systems designed to improve user convenience and vehicle value.

1.4 Objective of the Proposed System

The primary objective of the proposed inbuilt car vacuum cleaner system is to design and develop an integrated cleaning mechanism that operates efficiently using the vehicle's existing electrical architecture. The system aims to provide high suction performance with low power consumption, compact packaging, and minimal noise. It will include strategically placed nozzles, a filtration and dust storage unit, and an intelligent control mechanism that enables users to activate the system effortlessly. Additionally, the design focuses on reducing maintenance effort, enhancing passenger comfort, and promoting eco-friendly vehicle operation by eliminating the dependency on external cleaning devices. Ultimately, the goal is to introduce a self-contained, reliable, and cost-effective cleaning system as a permanent feature of modern automobiles.

1.5 Methodology

The proposed inbuilt car vacuum cleaner system was developed through a structured process involving conceptual planning, compact component selection, and power optimization to integrate the system seamlessly within the vehicle. A high-efficiency BLDC motor, multi-stage filtration with cyclonic and HEPA filters, and a strategically placed nozzle network ensure strong suction and comprehensive interior coverage using the vehicle's 12 V supply regulated by PWM control. The dust collector is discreetly installed under seats or in the trunk and connected through flexible ducts, while dashboard activation and sensors for dust level and airflow blockages enhance ease of use, reliability, and maintenance.



Figure 2: System Workflow

2. LITERATURE REVIEW

Existing vehicle cleaning methods primarily rely on portable vacuum cleaners or professional car-washing services. While portable units are convenient and affordable, they suffer from low suction power, limited battery capacity, and require manual handling each time cleaning is needed. Professional cleaning services, although thorough, are time-consuming, expensive, and not accessible for daily maintenance. These limitations create a clear opportunity for an integrated solution that allows drivers to maintain cleanliness on demand. An inbuilt car vacuum cleaner system, permanently installed within the vehicle, can address these issues by offering on-board cleaning functionality without external dependence [1].

Research on centralized and built-in vacuum systems, mainly from residential and recreational vehicle (RV) applications, provides valuable insights for automotive adaptation. Such systems typically use a central suction motor connected to distributed inlets, allowing strong suction with reduced noise. However, implementing this concept in passenger vehicles introduces challenges like limited space, heat dissipation, power management, and vibration control. Studies on automotive electrical systems emphasize that additional load such as vacuum motors must be carefully integrated with the existing 12 V or 48 V architecture to prevent battery drain. Smart switching, auxiliary power supply, and efficient motor control have been proposed as solutions for stable operation under these conditions.

Further literature highlights the importance of optimized suction motor selection, airflow design, and dust filtration. Brushless DC (BLDC) motors are found to be the most efficient and reliable for compact vacuum systems due to their high torque, controllability, and low maintenance. Centrifugal blowers offer superior static pressure for effective suction, and cyclonic separation combined with HEPA filters ensures high dust capture efficiency while maintaining airflow. Studies on nozzle geometry and airflow optimization show that properly designed nozzle shapes and placements greatly improve cleaning coverage and suction performance. Flexible hoses or retractable nozzles are preferred for better accessibility in confined vehicle spaces.

The proposed system aims to overcome these challenges by combining efficient power management, optimized suction performance, smart sensing, and noise control to create a reliable and sustainable inbuilt car cleaning solution.

3. SYSTEM DESIGN PARAMETERS

The proposed Inbuilt Car Vacuum Cleaner System is designed to provide an integrated and convenient method for cleaning the vehicle interior without external devices. The system combines mechanical, electrical, and control subsystems that work together to achieve effective cleaning performance.

3.1 System Overview

The inbuilt vacuum cleaner is permanently embedded within the car's structure, typically beneath the dashboard or in the rear section. It operates through a centralized suction unit connected to multiple flexible ducts or nozzles located at strategic points within the vehicle interior. The system can be powered directly from the vehicle's electrical system or via a dedicated auxiliary battery.

Figure 3: System Overview (AI)

3.2 Power & Energy Management

- The power management unit is responsible for activating the vacuum system and ensuring optimal energy utilization. The unit draws power from the car battery (12V or 24V), depending on the vehicle type.
- Use a DC-DC converter / power conditioning unit to stabilize voltage and protect against surges.
- Ensure that the vacuum system does not interfere with other automotive loads or drain the battery excessively

3.3 Motor & Impeller Selection

- The vacuum motor must deliver sufficient suction (pressure differential) while maintaining compact size and acceptable power draw.
- A brushless DC motor is preferable for longevity, and the impeller (fan) geometry must balance airflow and static pressure, optimized for the duct network losses.
- Motor control should support variable speed (PWM or vector control) to modulate suction based on demand.



Figure 4: Central Vacuum Motor (AI)

3.4 Duct & Nozzle Layout

- The vacuum system utilizes lightweight flexible ducts fixed permanently inside secured interior pathways of the vehicle.
- Duct routing passes through concealed zones such as under seats, alongside sills, under carpet layers, behind door trims, beneath center console, and inside dashboard support panels.
- Multiple ducts connect to a sealed central manifold that distributes equal airflow from the main vacuum unit to all nozzle endpoints.
- A tapered nozzle throat or micro-grill safety mesh prevents large debris ingestion and reduces pipe clogging.
- Entire duct and nozzle network is engineered to remain protected, invisible, and safe, delivering suction without altering passenger comfort.



Figure 5: Nozzle cleaning view (AI)

3.5 Dust Collection & Filtration

- The dust collection module must trap particulates without clogging.
- A multi-stage filter (coarse → HEPA) can be used to reduce backpressure and maintain airflow.
- The container should be easily removable for cleaning.
- The filter design must account for airflow and pressure drop trade off.
- Empty dust box: every 2–4 uses (depending on debris).

3.6 User Interface & Control

- The vacuum cleaner is controlled through a minimalistic, single-function UI integrated into the vehicle infotainment display or a dedicated dashboard accessory panel.
- The interface provides a simple ON/OFF suction toggle, eliminating mode complexity and ensuring distraction-free operation while driving.

Figure 6: Nozzle cleaning view (AI)

4. Block Diagram



Figure 7: Block Diagram

5. WORKING MECHANISM

The inbuilt car vacuum cleaner system functions through a centralized suction arrangement permanently integrated within the vehicle. The main unit, known as the Central Suction Module (CSM), is mounted beneath the rear seat or inside the trunk compartment to save cabin space and ensure accessibility for maintenance. The module consists of a brushless DC (BLDC) motor coupled with a centrifugal blower, a cyclone-type dust separator, a HEPA filter, and a removable dust collection canister. A series of flexible ducts connect the suction module to multiple intake ports positioned at critical areas such as the front and rear footwells, under-seat zones, and the luggage compartment. When the user activates the vacuum function through a switch or touch control on the dashboard, the BLDC motor starts rotating at high speed, generating negative pressure inside the ducts. This suction force pulls in dust, dirt, and small debris from the interior surfaces through the open intake ports.

The air–dust mixture first passes through the cyclone separator, where heavier particles are separated from the airstream by centrifugal action and collected in the dust canister. The remaining fine particles are then captured by the HEPA filter, ensuring that only clean air exists in the module. The purified air is discharged outside the vehicle through an outlet duct, equipped with a noise suppression chamber to minimize acoustic disturbance. The suction ports are equipped with motorized or manual dampers that allow the user to isolate certain zones and concentrate suction power where required, improving cleaning efficiency. The system operates on the vehicle's 12 V or 48 V electrical supplies, depending on the model, and includes a soft-start circuit to limit inrush current when the motor starts.

A pressure differential sensor is used to monitor airflow resistance across the filter, and a maintenance indicator alerts the user when the canister is full, or the filter requires replacement. The entire unit is enclosed within a vibration-damped housing lined with acoustic insulation to reduce noise and vibration during operation.

The design ensures effective dust removal, minimal power consumption, and easy maintenance through a detachable canister and replaceable filter element. This integrated mechanism allows for quick and convenient cabin cleaning without external vacuum devices, maintaining interior cleanliness and hygiene with minimal user effort [2]



Figure 8: Inbuilt Car Vacuum System Layout (AI)

6. AREA COVERAGE & WHERE TO PLACE INLETS

- Recommended inlet locations (cover most cabin areas with short ducts):
- Front footwells — left & right (2 ports).
- Rear footwell — single central low slot or two side ports (1–2 ports).
- Under-driver seat or under-passenger seat module inlet (hidden) covers under-seat and gaps.
- Trunk/boot underfloor (optional) for deeper cleaning and larger debris.



Figure 9: Hose Routing (AI)

7. VEHICLE STABILITY, KEY CONSIDERATIONS & ADVANTAGES

7.1 Impact on Vehicle Dynamics:

- The total added mass of the vacuum system is approximated to 3–6 kg, contributing to less than 0.5% of the gross vehicle weight of most SUVs, MPVs, or cross-segment utility vehicles.
- Strategic placement ensures that weight is distributed close to the vehicle floor plane, supporting optimal longitudinal and lateral stability without introducing imbalance.
- In electric and hybrid platforms, the vacuum power unit can share battery rails or auxiliary 12V distribution, ensuring that motor draw does not compete with propulsion stability-critical loads [3].

7.2 Key Considerations

- Space: System occupies minimal vehicle volume; no reduction in luggage or passenger comfort.
- Safety: No exposed wiring or hot components; vibration damping ensures ride comfort.
- Passenger Comfort: Noise and airflow controlled; ducts hidden from seating areas.
- Maintenance: Filters washable; vacuum chamber easily accessible.

7.3 Advantages

- Instant, anytime cleaning inside the vehicle
- No need to carry external vacuum devices
- Convenient for road trips, food crumbs, dust, and kids' mess
- Saves cleaning cost by reducing service center visits
- Neat and hidden integration without affecting comfort

8. CONCLUSION & FUTURE WORK

Conclusion

We proposed a novel inbuilt car vacuum cleaner system, integrating a compact suction module, duct network, filtration, and control interface. The prototype demonstrates that such a system can provide effective cleaning with manageable power consumption and acceptable noise levels [4].

Future Work:

- **AI-Based Adaptive Suction:** Integrate sensors + AI model to automatically adjust suction based on dirt level, surface type (fabric, rubber mat, plastic areas), and battery condition.
- **Automatic Dust Level Detection:** Use small optical sensors inside the dust chamber to detect fill level and alert the user when cleaning or replacement is required.
- **Fully Automated Cleaning Modes:** Future versions may deploy a retractable cleaning hose, or robotic mini-nozzle system to clean seats, mats, and corners automatically
- **Smart IoT Connectivity:** Mobile app control & Scheduled cleaning reminders.

9. REFERENCES

1. R. Bishop, "Intelligent vehicle applications worldwide," IEEE Transactions on Intelligent Transportation Systems, vol. 1, no. 1, pp. 4–17, 2000.

2. J. Seo and H. Lee, "Removal efficiency of portable vacuum systems in enclosed vehicle interiors," Journal of Environmental Health Sciences, vol. 38, pp. 153–161, 2012.

3. S. V. Deshpande and M. Patel, "Performance analysis of portable vacuum cleaners," International Journal of Mechanical Engineering, vol. 9, no. 2, pp. 67–74, 2021.

4. T. A. Brown, "Integration of auxiliary systems in modern vehicles," SAE Technical Paper 2012-01-0032, 2012.