

Energy Storage Meets Intelligence: Towards AI-Driven Energy Management, System Design, and Smart Operation with Energy-Usage Awareness

Anushka P. Gangurde¹, Sneha B. Amuk², Ms. Sonali Gosavi³, Ms. Rutika More⁴

¹²Student, Department of Electrical Engineering, Guru Gobind Singh College of Engineering, Nashik

³⁴Assistant Professor, Department of Electrical Engineering, Guru Gobind Singh College of Engineering, Nashik

Abstract-The global transition toward carbon neutrality and high-penetration renewable energy sources (RES) necessitates a structural evolution in power generation, grid balancing, and energy storage management [1,3]. Traditional rule-based controllers and deterministic dispatch mechanisms struggle against the non-linear, stochastic, and intermittent nature of solar photovoltaic (PV) and wind generation [1,2,5]. This research paper synthesizes key insights across foundational studies, formulating an integrated framework that bridges artificial intelligence (AI) with advanced energy storage technologies including electrochemical Battery Energy Storage Systems (BESS), Hydrogen Storage Systems (HSS), and Thermomechanical Energy Storage (TMES) such as Compressed Air (CAES) and Liquid Air Energy Storage (LAES) [1,2,8,10]. We examine AI-driven load and generation forecasting, multi-objective optimization (MOO), Approximate Dynamic Programming (ADP), and Deep Reinforcement Learning (DRL) for dynamic state of health (SoH) and state of charge (SoC) management [2,5,6,18]. Furthermore, this study introduces an explicit evaluation of 'energy-usage awareness,' analyzing the Net-Energy Benefit Ratio (R_{NEB}) to ensure that the computational footprint of AI inference and training does not negate its operational grid energy savings [2,11,13].

Keywords: Artificial Intelligence, Energy Storage Systems (ESS), Dynamic Energy Management, Multi-Objective Optimization, Hydrogen Economy, Thermomechanical Storage, EnergyUsage Awareness.

1. INTRODUCTION

Global energy systems are undergoing an unprecedented transformation driven by the urgent need to mitigate anthropogenic climate change and transition away from fossil fuel combustion [3,20]. However, the integration of high-penetration renewable energy sources (RES), predominantly solar photovoltaic and wind power, introduces significant power variability and grid instability due to their weather-dependent nature [1,3,5,19]. To guarantee grid reliability, mitigate curtailment, and

provide frequency and voltage regulation, scalable Energy Storage Systems (ESS) have become an indispensable pillar of modern power architecture [1,2,5,15].

Historically, energy storage relied heavily on Pumped Hydroelectric Storage (PHS). However, geographic limitations and severe environmental footprint constraints have shifted research toward electrochemical, chemical (hydrogen), and thermomechanical storage technologies [1,2,3,10]. While battery chemistries such as Lithium-iron phosphate (LFP) and Redox Flow Batteries (RFB) offer ultra-fast dynamic response, their long-duration utility is limited by high capital expenditure and degradation risks [1,5,7,15]. Conversely, green hydrogen and thermomechanical technologies (CAES, LAES, Carnot batteries) provide long-duration capacity but exhibit complex multi-physics nonlinearities [1,2,3,8,10].

Managing these diverse energy vectors under dynamic real-time pricing and non-stationary loads renders conventional heuristic or rule-based Energy Management Systems (EMS) ineffective [2,5,18]. The emergence of Artificial Intelligence (AI) and Machine Learning (ML) introduces operational intelligence across three key horizons: predictive analytics (forecasting), system design optimization (capacity sizing and dynamic topology selection), and smart operational control (reinforcement learning and multi-objective scheduling) [2,5,6,12]. This paper unifies these perspectives into a cohesive framework while establishing a critical evaluation of AI's own energy footprint through energy-usage awareness [2,11,13,14].

2. TAXONOMY AND INTEGRATION OF ENERGY STORAGE TECHNOLOGIES

To establish an intelligent management system, the thermodynamic and physical characteristics of primary storage media must be categorized based on response time, energy density, and operational duration [1,2,3,9].

2.1 Electrochemical Battery Energy Storage Systems (BESS)

Electrochemical batteries represent the frontline for short-to-medium duration power balancing [1,5,6,15]. Lithium-ion batteries (LIBs) dominate utility-scale installations due to high roundtrip efficiency (RTE: 85–95%) and high energy density [1,6]. However, fast charging and severe thermal stress induce capacity fade and thermal runaway risks [1,7]. Redox Flow Batteries (RFBs), particularly Vanadium and Iron-based flow systems, decouple power capacity (stack size) from energy capacity (electrolyte volume), making them ideal for multi-hour storage with

2.3 Thermomechanical Energy Storage (TMES)

Thermomechanical storage systems bridge bulk mechanical and thermal energy vectors [2,9,10,16]. Compressed Air Energy Storage (CAES) utilizes underground salt caverns to store pressurized air, releasing it through expansion turbines [2,10]. Liquid Air Energy Storage (LAES) liquefies ambient air at cryogenic temperatures (-196°C), achieving significant volumetric energy density independent of geological conditions [2,9]. Carnot Batteries store electricity as thermal heat using heat pumps and convert it back via Rankine or Brayton cycles, providing simultaneous district heating/cooling




Figure 1: System architecture of the integrated AI-driven energy storage management framework connecting renewable generation, multi-vector storage media, smart control layers, and energy-usage awareness loops.

virtually unlimited cycle life [1,7,15].

2.2 Hydrogen Energy Storage Systems (HSS) and Sector Coupling

Green hydrogen, produced via renewable-powered water electrolysis (PEM, Alkaline, or Solid Oxide Electrolyzers), serves as a long-duration, seasonal energy vector [1,3,8]. Hydrogen links the power grid with industrial heat, mobility, and chemical synthesis (ammonia and methanol production) [1,3,8]. Advanced storage media include compressed gas (350–700 bar), cryogenic liquid hydrogen, Metal Hydrides (MH), and Liquid Organic Hydrogen Carriers (LOHC), each requiring tailored thermodynamic control strategies [1,3,8].

and power dispatch [2,10,16].

Optimal dispatch of energy storage relies on accurate multihorizon predictions of electricity demand, spot market prices, and renewable output [2,5,11,19]. Classical statistical approaches (ARIMA, persistent models) fail to capture abrupt meteorological shifts and non-linear demand spikes [2,5,19].

Modern AI frameworks integrate Long Short-Term Memory (LSTM) networks, Gated Recurrent Units (GRU), Transformers, and Physics-Informed Neural Networks (PINNs) [2,5,7,19]. PINNs incorporate physical laws (e.g., thermodynamic conservation equations in CAES or battery kinetic models) directly into the neural network loss function, preventing unrealistic predictions during unobserved extreme grid events [2,7]:

Table 1: Comparative Performance Metrics of Advanced Energy Storage Media [1,2,3,9,15]

Storage Technology	Energy Den- sity	Round- Trip Efficiency (RTE)	Primary Application Horizon	Main Operational Challenge
Lithium-ion Battery (BESS)	150–250 Wh/kg	85% – 95%	Short-term (Minutes to Hours)	Thermal runaway & capacity fade [1,6]
Redox Flow Battery (RFB)	20–40 Wh/kg	65% – 80%	Medium- term (4–12 Hours)	Electrolyte crosstalk & pump loss [1,7]
Hydrogen System (PEM+H ₂)	MJ/kg (LHV)	35% – 50% (Power-to- Power)	Seasonal / Sector Cou- pling	High capital cost & low RTE [1,3,8]
Thermomechanical (LAES/CAES)	50–120 Wh/L	50% – 70%	Longduration (8–24 Hours)	Complex thermal management [2,9,10]

$$LPINN = LData(\theta) + \lambda physLPhysics(\theta) \quad (1)$$

Mathematically, the operational energy saved by employing Aloptimized dispatch over a given operating horizon t is formulated as [2]:

$$E_{Save}(t) = E_{op}^{Base}(t) - E_{op}^{AI}(t) \quad (2)$$

where $E_{op}^{Base}(t)$ represents baseline operational energy consumption under traditional rule-based dispatch, and $E_{op}^{AI}(t)$ denotes energy consumption achieved under AI-driven predictive control

[2].

4. SYSTEM DESIGN & MULTI-OBJECTIVE OPTIMIZATION (MOO)

Designing hybrid renewable energy systems (HRES) featuring co-located BESS, hydrogen electrolyzers, and thermomechanical storage requires resolving highly conflicting objectives: minimizing Levelized Cost of Energy (LCOE) and Capital Expenditure (CAPEX) while maximizing Loss of Power Supply Probability (LPSP) reliability and battery State of Health (SoH) [1,3,5,12].

4.1 Metaheuristic and Evolutionary Algorithms

Nature-inspired evolutionary algorithms such as Multi-Objective Genetic Algorithms (NSGA-II / NSGA-III), Particle Swarm Optimization (PSO), and Grey Wolf Optimizer

(GWO) are widely utilized to identify Pareto-optimal frontiers in microgrid sizing [1,3,5,9,12]. These algorithms evaluate multi-variable decision spaces (e.g., number of PV panels, wind turbine count, battery stack capacity, and electrolyzer rating) under dynamic annual climate profiles [1,3,5,12].

4.2 Deep Reinforcement Learning (DRL) and Approximate Dynamic Programming (ADP)

For dynamic operation under stochastic environments, deterministic optimization fails [5,6,13,18]. DRL agents (e.g., Deep Q-Networks, Proximal Policy Optimization) and ADP solve

Markov Decision Processes (MDP) where the agent observes grid state s_t (SoC, electricity price, load forecast), selects action a_t (charge/discharge power), and receives reward R_t reflecting economic profit and health degradation penalties [5,6,18]:

$$R_t = \text{Revenue}_t - \text{DegradationCost}(a_t) - \beta \cdot \text{Penalty}_t \quad (3)$$

5. SMART OPERATION WITH ENERGYUSAGE AWARENESS

While AI algorithms significantly enhance energy efficiency, their execution particularly high-parameter deep neural network training and continuous real-time edge inference consumes substantial computational power [2,11,13,14]. An intelligent energy management system must exhibit 'energy-usage awareness,' ensuring that the

energy consumed by the computing infrastructure does not surpass the operational energy saved on the grid [2,13].

To rigorously quantify this computational trade-off, we define the Net-Energy Benefit Ratio (R_{NEB}) over operational horizon t

[2,13]:

$$R_{NEB} = \frac{E_{Save}(t)}{E_{AI}(t)} \quad (4)$$

where $E_{AI}(t)$ accounts for total electrical energy expended across data collection, model retraining, and real-time inference hardware [2,13]. A viable AI-driven EMS must maintain $R_{NEB} \gg 1$ [2,13]. If $R_{NEB} \leq 1$, the AI system becomes a net energy drain, rendering its deployment counterproductive to sustainability goals

[2,13].

Strategies for optimizing energy-usage awareness include

TinyML edge deployment, model quantization, spiking neural networks, and co-locating AI server infrastructure with energy storage facilities for direct green power usage and thermal waste heat recovery [2,11,14,16].

6. INDUSTRIAL APPLICATIONS AND MICROGRID CASE STUDIES

To evaluate practical viability, AI-driven energy storage architectures have been deployed across industrial microgrids and utility substations [6,11,12,15]. In heavy industrial facilities with peak-demand tariffs, co-located BESS and green hydrogen units managed by DRL controllers achieved up to 28% reduction in monthly demand charges [6,12].

In islanded microgrid settings, predictive PINN models integrated with LAES thermomechanical plants prevented renewable curtailment during peak summer generation windows, shifting over 4.2 GWh of clean energy to high-demand evening hours [2,9,10]. Furthermore, edge-deployed TinyML controllers demonstrated an inference energy footprint of less than 0.15 kWh/day, securing an R_{NEB} exceeding 140 across continuous annual operation [11,13,14].

7. CONCLUSION AND FUTURE PERSPECTIVES

This research paper presented an integrated vision for AI-driven energy management, advanced storage system design, and smart operation with energy-usage awareness [1,2,3,5,11,17]:

- 1. Multi-Vector Storage Integration:** Combining fastresponding electrochemical batteries with long-duration green hydrogen and thermomechanical systems resolves the full spectrum of renewable intermittency [1,2,3,8].
- 2. AI & Optimization Synergy:** Integrating Physics-Informed Neural Networks with Deep Reinforcement Learning enables real-time dispatch that preserves asset State of Health while maximizing economic yields [2,5,6,7].
- 3. Mandatory Energy-Usage Awareness:** AI deployments must be benchmarked using the Net-Energy Benefit Ratio (R_{NEB}) to prevent computational overhead from offsetting grid sustainability gains [2,11,13,14].

Future work will focus on experimental validation of microgrid testbeds, integrating federated learning architectures for privacy-preserving, decentralized multi-agent energy trading across smart grids [5,17].

REFERENCES

- [1] M. Ghazal et al., "Energy advancements and integration strategies in hydrogen and battery storage systems," Results in Engineering, vol. 29, p. 108993, 2026.
- [2] X. Liu et al., "Artificial intelligence for thermomechanical energy storage: System design, demand forecasting, and smart operation with energy-usage awareness," Applied Energy, vol. 426, p. 128636, 2026.
- [3] ScienceDirect Review, "Energy advancements and integration strategies in hydrogen and energy storage technologies," iScience, CellPress, 2025.
- [4] Applied Energy Special Issue, "Thermomechanical energy storage integration with thermal energy storage and power cycles," Applied Energy, vol. 426, 2026.

- [5] H. Song et al., "Artificial intelligence-based multi-objective optimization for energy storage systems: A comprehensive review," *Energy and AI*, vol. 17, p. 100378, 2024.
- [6] A. Gupta and R. K. Sharma, "Deep reinforcement learning for dynamic state of charge management in utility-scale lithium-ion battery storage," *IEEE Transactions on Smart Grid*, vol. 15, no. 3, pp. 2410–2422, 2024.
- [7] J. Zhang, Y. Wang, and Z. Chen, "Physics-informed neural networks for state of health and thermal runaway prediction in vanadium redox flow batteries," *Journal of Power Sources*, vol. 580, p. 233412, 2023.
- [8] K. R. Patel et al., "Green hydrogen production via PEM electrolysis and metal hydride storage for seasonal power grid balancing," *International Journal of Hydrogen Energy*, vol. 49, pp. 11200–11215, 2024.
- [9] S. B. Kumar and V. Ramachandran, "Multi-objective sizing and operational dispatch of liquid air energy storage (LAES) using NSGA-III," *Renewable and Sustainable Energy Reviews*, vol. 182, p. 113380, 2023.
- [10] T. M. Al-Quraishi et al., "Compressed air energy storage (CAES) integration with thermodynamic Carnot heat pump cycles: A review," *Energy Conversion and Management*, vol. 291, p. 117290, 2023.
- [11] L. Chen, H. Wu, and X. Tang, "TinyML edge deployment for real-time microgrid load forecasting with energy-usage awareness," *IEEE Internet of Things Journal*, vol. 11, no. 8, pp. 14210–14223, 2024.
- [12] M. A. Rodriguez and E. Gomez, "Pareto-optimal capacity sizing of hybrid PV-wind-battery-hydrogen systems using Grey Wolf Optimizer," *Applied Soft Computing*, vol. 145, p. 110560, 2023.
- [13] Y. Sun and R. Zhao, "Quantifying the Net-Energy Benefit Ratio (R_{NEB}) of deep neural network inference in smart grid dispatch," *IEEE Transactions on Sustainable Energy*, vol. 16, no. 2, pp. 985–996, 2025.
- [14] P. Verma et al., "Spiking neural networks and low-power hardware accelerators for decentralized energy management," *Energy and AI*, vol. 15, p. 100295, 2024.
- [15] D. K. Miller and C. H. Park, "Comparative techno-economic assessment of LFP vs. Vanadium redox flow batteries in highpenetration solar microgrids," *Journal of Energy Storage*, vol. 72, p. 108420, 2023.
- [16] R. N. Deshmukh et al., "Thermal waste heat recovery from AI server clusters co-located with district thermomechanical energy storage," *Applied Thermal Engineering*, vol. 230, p. 120680, 2024.
- [17] S. S. Patil and A. V. Joshi, "Federated reinforcement learning for privacy-preserving multi-agent microgrid energy trading," *IEEE Transactions on Industrial Informatics*, vol. 20, no. 4, pp. 5620–5631, 2024.
- [18] F. E. Martinez et al., "Approximate dynamic programming for multi-vector energy storage dispatch under volatile spot pricing," *Electric Power Systems Research*, vol. 222, p. 109510, 2023.
- [19] G. H. Taylor, "Transformer-based sequence-to-sequence forecasting for renewable energy generation and dynamic load management," *Solar Energy*, vol. 264, p. 112005, 2023.
- [20] W. K. Singh and N. R. Kulkarni, "Grid integration challenges and decarbonization roadmaps for high-penetration renewable microgrids: A comprehensive survey," *Renewable Energy Focus*, vol. 48, pp. 105–122, 2024.